Technical data sheet

GES4 service outlet with locking slider

Item number: 7405146





Service outlet with locking slider for up to 6 individual Modul 45 devices in 2 UT3 universal supports, use in duct systems and system floors for indoor use.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 3, 8 or 10 mm.

Up to 4 installation devices can be used with 50 mm central plate.

Service outlet with locking slider, 2-compartment, for the installation of MT4 mounting support. Two type APMT2 cover plates can be installed.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 3, 8 or 10 mm.





Polyamide

Master data

Item number	7405146
Description 1	Service outlet
Description 2	for universal mounting
Manufacturer	OBO
Dimension	222x222x65
Colour	Graphite black; RAL 9011
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	124 kg
Weight unit	kg/100 pc.

Technical data sheet

GES4 service outlet with locking slider



Technical data



Dimensions Length Width 2222 mm Height 65 mm

	Number of installable devices	6
	Number of mounting boxes	2
	Version for	Square
	Cable outlet version	Swivellable cord outlet
	Floor covering protection frame	yes
	Floor care	Dry
	Seal installation option	no
	Screed height, min.	73 mm
	Floor height, min.	73 mm
	Suitable for raised floor installati-	yes
	on Suitable for screed-flush closed	no
	underfloor ducts	no
	Suitable for screed-covered underfloor ducts	yes
	Suitable for cavity floor installation	yes
	Suitable for wet care	no
	Suitable for underfloor box	250/350
	Suitable for underfloor ducts	yes
	Device support to accept mounting boxes	yes
	Length of external dimensions	222 mm
	Length of installation dimensions	201 mm
	With floor covering recess	yes
	Nominal size for device installation units	4
	Frame version	Carpet protection frame
	Protection rating (IP) when used	IP20
	Protection rating (IP) when unused	IP40
	Protection rating IK code	IK08
	Heavy-duty version	no
	Installation system type	UT3

Technical data sheet

GES4 service outlet with locking slider





Technical data				
Vertical load, large area	to 3,000 N			
Vertical load, small area	to 2,000 N			
Approvals	VDE			
Opening mechanism	Locking slider			
Floor covering thickness	5 mm			