## **Technical data sheet**

# Underfloor duct, 2 pieces, 2-compartment, duct height 48 mm

**Item number: 7400261** 



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable duct cover. With separating retainer in the duct base.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.





St

Steel

FS

Strip galvanized

### Master data

Item number	7400261
Description 1	Underfloor duct, 2-part
Description 2	2 compartments
Manufacturer	OBO
Dimension	2000x190x48
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	347.997 kg
Weight unit	kg/100 m

#### **Dimensions**

Length	2,000 mm
Width	190 mm
Height	48 mm
Dimension a	80 mm
Dimension b	110 mm
Dimension h	48 mm

## **Technical data sheet**

Underfloor duct, 2 pieces, 2-compartment, duct height 48 mm

**Item number: 7400261** 



Technical data		
	Number of fixed partitions	1
	Number of compartments	2 St.
	Mounting system fastening type	Floor
	Floor plate	yes
	Application area	Screed-covered
	Decouplable	no
	Trunking width, min.	190 mm
	Duct height, min.	48 mm
	Usable cross-section	8217 mm²
	Removable cover	yes
	Cross-section, draw a	3413 mm²
	Cross-section, draw b	4804 mm²